

PLATINUM PLUS CUSTOM BELT ORDER FORM



BLACK BELTS ONLY. Complete online or print, complete, scan and email to custombelts@teamsimpson.com. We will call you with an estimate before beginning work on your belts. Questions?, call 800-654-7223

| | | | | |
|--------------|---------------|---------------|---------------------|---------------------|
| NAME: | PHONE: | EMAIL: | TYPE OF CAR: | SALES ORDER: |
|--------------|---------------|---------------|---------------------|---------------------|

| | | | | | |
|-----------------------------|--------------------|----------|----------|------------------|----------------------|
| STEP 1 CERTIFICATION | SFI RATING: | | | MATERIAL: | |
| | SFI 16.1 | SFI 16.5 | SFI 16.6 | LIGHT | HEAVY (OVER 200 LBS) |

| | | | | | | |
|---|--------------------------|-------|------------------------|-------|---------------------|----|
| STEP 2 LAP BELT STYLE <small>For fixed length, non-adjustables: Call 1.800.473.7077</small> | SINGLE PULL DOWN: | | SINGLE PULL UP: | | DOUBLE PULL: | |
| | LEFT | RIGHT | LEFT | RIGHT | DOWN | UP |

| | | |
|------------------------------|--------|--------|
| STEP 3 LAP BELT WIDTH | 3 INCH | 2 INCH |
|------------------------------|--------|--------|

| | | | |
|----------------------------------|----------|-------|-------------|
| STEP 4 LAP BELT ADJUSTERS | ALUMINUM | STEEL | SEWN ANCHOR |
|----------------------------------|----------|-------|-------------|

| | | | |
|------------------------------|---------|---------|-------------|
| STEP 5 LAP BELT MOUNT | BOLT IN | CLIP IN | WRAP AROUND |
|------------------------------|---------|---------|-------------|

| | | | | |
|-------------------------------|---------------|--|-------------------------------------|--------------|
| STEP 6 LAP BELT LENGTH | UNIVERSAL | | ADJUSTER (SHORT LAP LENGTH): | |
| | CUSTOM: _____ | | IN SEAT | OUTSIDE SEAT |

| | | | | |
|---------------------------|---------------------------|--|----------------------|--------------------|
| STEP 7 BUCKLE TYPE | LATCH & LINK | LATCH & LINK <small>DBL. PULL DOWN ONLY</small> | CAM LOCK STANDARD | ROTARY CAM LOCK |
| | | | | |
| | CAM LOCK LOCATION: | | RIGHT SIDE | BOTTOM |

SUB BELTS

| | | | |
|-------------------------------|---|---|---|
| STEP 8 MOUNTING POINTS | 5 | 6 | 7 |
|-------------------------------|---|---|---|

| | | | |
|-----------------------------|---------|-------|--------|
| STEP 9 MOUNTING TYPE | FORMULA | T BAR | V TYPE |
|-----------------------------|---------|-------|--------|

SHOULDER BELTS

| | | | |
|---------------------------|--------|--------|---------------|
| STEP 10 BELT WIDTH | 2 INCH | 3 INCH | DUAL SHOULDER |
|---------------------------|--------|--------|---------------|

| | | |
|------------------------------|----------|-------|
| STEP 11 BELT ADJUSTER | ALUMINUM | STEEL |
|------------------------------|----------|-------|

| | | | |
|---------------------------|-------------------|-----------|-------------------------|
| STEP 12 BELT MOUNT | BOLT IN (W/3 BAR) | CLIP IN | WRAP AROUND (NO ANCHOR) |
| | SEWN ANCHOR | SEWN LOOP | |

| | | | |
|----------------------------|------------------------|---------------|--|
| STEP 13 BELT LENGTH | STANDARD (MOST COMMON) | CUSTOM: _____ | |
|----------------------------|------------------------|---------------|--|

| | | | |
|--------------------------|--------------------------|------------------|--------------------------------|
| STEP 14 BELT PULL | FOLD OVER | LOOP | COVERED WITH NOMEX® (OPTIONAL) |
| | TITANIUM SPACERS: | | |
| | STEP BUSHING | SHOULDER BUSHING | SHOULDER COMBO SET |